

EVOKO MINTO

Technical specifications

COLORS

Soft White



Deep Grey



AUDIO

Patented sound-improvement software and four directive microphones for state of the art echo cancellation, noise reduction and speech enhancement

Advanced patented processing/microphone mixing

- Full Duplex (FDX)
- Acoustic Echo Cancellation (AEC)
- Line Echo Cancellation (LEC)
- Noise Reduction (NR)
- Automatic Gain Control (AGC)
- Equalizer (EQ)
- Comfort Noise Generator (CNG)
- Automatic Microphone Mixing (AMM)

Range

- Covering a radius of 5 m (16 ft)
- Rooms for more than 20 persons

Frequency

- 100 Hz to 22 kHz

Speaker effect

- 2 W

Volume

- Adjustable in 10 steps

PROCESSORS

Dual processors with dedicated DSP for sound processing to deliver uncompromised performance

System controller

- ARM™ Cortex M3 based MCU

DSP

- Audio processing done in Analog Devices SHARC DSP

CONNECTIVITY

Easily connect directly with your own device

Bluetooth

- v2.1
- Power Class 2
- HFP v1.6 for speech supporting High Quality Audio (mSBC codec)
- A2DP for music playback

USB

- v 2.0 HS
- Audio Device Class (UAC)

Audio Cable

- Analog Audio Interface through 4-pole 3.5 mm connector
- CTIA standard
- Compatible with the majority of smartphones

POWER

Ready to be used anywhere in the office

Battery

- 8 hours talk time
- Auto power off after 10 minutes inactivity
- Fully charged in 6 hours (empty to full)
- Rechargeable 3.7 V Li-Ion battery with 3400 mAh capacity

Charge via Wall Mount/Portable Charger

- Input: AC 100-240 V, 50/60 Hz, 0.5 A
- Max output: 5 VDC, 3.0 A

Charge via USB

- If connected to a computer

HALO LIGHT

Distinctive light feedback to make the status clear to everyone at the table

Blue

- Flashing: Bluetooth pairing
- Fixed: Connected

Green

- Active call

Red

- Microphones on mute

Purple

- Backlight when charging on Wall Mount (optional)

EVOKO MINTO

VOICE FEEDBACK

Minto has clear voice feedback; letting you know e.g. the battery status or how to connect

Select Voice Feedback mode

- Normal: Information about the status or activity
- Limited: Critical information only

Languages

- Chinese (Mandarin)
- English
- French
- German
- Italian
- Russian
- Spanish
- Swedish

DIMENSIONS AND WEIGHTS

Minto unit

- Diameter: 240 mm (9.4 in)
- Height: 50 mm (2.0 in)
- Weight: 1.1 kg (2.4 lb)

Wall Mount

- Length: 110 mm (4.3 in)
- Width: 85 mm (3.3 in)
- Height: 40 mm (1.6 in)
- Weight: 0.3 kg (0.6 lb) (incl. charger and cable)

Gift box

- Length: 342 mm (13.5 in)
- Width: 279 mm (11.0 in)
- Height: 99 mm (3.9 in)
- Weight: 2.0 kg (4.4 lb)

Master box (4 pcs)

- Length: 416 mm (16.4 in)
- Width: 294 mm (11.6 in)
- Height: 368 mm (14.5 in)
- Weight: 9.2 kg (20.3 lb)

ENVIRONMENTAL CONDITIONS

Please note that Evoko Minto is built for indoor use!

Operating/Charging temperature

- 0° C to +40° C (32° F to 104° F)

Relative humidity

- 90% non-condensing

SHIPS WITH

Included in gift box

- Evoko Minto unit
- Wall Mount which plugs into AC/DC outlet with 3 m (12 ft) cable

- USB to Micro USB cable
- 4-pole 3.5 mm Audio Cable
- Quick Start Guide

ACCESSORIES AND SPARE PARTS

Portable Charger

- For charging on other places than on Wall Mount

Wall Mount

- If extra is needed, includes charger and cable

USB to Micro USB cable

- If extra is needed

4-pin 3.5 mm Audio Cable

- If extra is needed

Battery

- For replacement of old one

OTHER INFORMATION

Country of origin

- Developed in Sweden
- Manufactured in China

Warranty

- 2 years from date of purchase

Color versions

- Evoko Minto Soft White
- Evoko Minto Deep Grey

Upgrades

- Firmware upgrades through Evoko Control Panel (for Microsoft Windows) via USB connection.